



Loose Lay format available in all LSI patterns listed below

Data Specification Information

Square	Tile size	Tile thickness	Edge type	Carton size	Pieces per carton	Weight per carton
Antique Woods, Bamboo, Clovelly CLL42511, CLL42512, CLL42516, Concrete, Cork, Cow, Earth Woods, Elements, Finger Print, Hammered Aluminum, Healthcare Wood, Natural Woods, Rusted Steel, Solids, Sparkly Chips, Stained Concrete, Tadao & Ando, Tread Plate, Weathered Concrete	24" x 24" / 609.6 x 609.6mm	0.197" / 5mm	Straight	24 ft ² / 2.23 m ²	6 squares	47.3lb / 21.5kg
Plank						
Antique Woods, Bamboo, Earth Woods, Natural Woods	6" x 36" / 152.3 x 914.4mm	0.197" / 5mm	Straight	21 ft ² / 1.95 m ²	14 planks	40.7lb / 18.5kg
Healthcare Wood Weathered Concrete	6" x 48" / 152.3 x 1219.2mm	0.197" / 5mm	Straight	20 ft ² / 1.86 m ²	10 planks	39.2lb / 17.8kg
Parallelogram	24" x 41.57" / 609.6 x 1055.88mm	0.197" / 5mm	Straight	10.4 ft ² / 0.965 m ²	3 pieces	21.5lb / 9.8kg
Hexagon	20.8" x 24" / 527.9 x 609.6mm	0.197" / 5mm	Straight	15.6 ft ² / 1.45 m ²	6 pieces	30.8lb / 14kg
Chevron	8" x 24" / 203.2 x 609.6mm	0.197" / 5mm	Straight	10.4 ft ² / 0.965 m ²	9 pieces	20.9lb / 9.5kg
Antique Woods, Bamboo, Clovelly CLL42511, CLL42512, CLL42516, Concrete, Cork, Cow, Earth Woods, Elements, Finger Print, Hammered Aluminum, Healthcare Wood, Natural Woods, Rusted Steel, Solids, Sparkly Chips, Stained Concrete, Tadao & Ando, Tread Plate, Weathered Concrete						

Technical Standards

	ASTM and EN Standard	Result		ASTM and EN Standard	Result
Wear Group	EN 685	Class 34,43	Acoustical Impact Noise Reduction	ASTM E492-09 EN ISO 717-2	IIC 46 22dB
Caster Chair	ASTM D6962	(10,000 cycles) 4.5 (scale 1-5)	Color Fastness	ASTM F1515 ISO 105-B02-3	Exceeds requirements ≥ 6
Slip Resistance	ASTM D2047 DIN 51130 EN 13893	ADA Compliant R10 ≥ 0.3	Dimensional Stability	ASTM F2199 EN 434	Exceeds requirements ≤ 0.25%
Residual Indentation	ASTM F970 EN 433 ASTM F1914-98	(250 lbs) 0.003" 0.07 mm (Residual indentation at 75 lbs) - 0.002"	Flexibility	ASTM F137 EN 435	Pass Pass
Chemical Resistance	ASTM F925 EN 423	Excellent Excellent	Smoke Generation	ASTM E662	< 450
			Fire Rating	ASTM E648 DIN 4102 EN 1350-1	Class 1 B 1 B _n -s1

Expressive floors™

tel: 416.299.7666
toll-free: 1.800.449.3916
lsifloors.com