

## Technical Data

**TECHNICAL INFORMATION FOR CUSTOM PRINTED VINYL FLOORING**

	<b>ISO and EN STANDARD</b>	<b>TEST RESULT</b>
<b>Total Thickness</b>	ISO 24346/EN428	0.79" / 2 mm
<b>Thickness Wear layer</b>	ISO 24340/EN429	0.79" / 2 mm
<b>Commercial Use</b>	ISO 10874/EN685	Class 34 very heavy
<b>Industrial Use</b>	ISO 10874/EN685	Class 43 heavy
<b>Roll Width</b>	ISO 24341/EN426	10 ft. / 3.04 m
<b>Roll Length</b>	ISO 24341/EN426	50 ft. / 15.24 m
<b>Total Weight</b>	ISO 23997/EN430	1.72 lbs/sq.ft. / 2.83 kg/m <sup>2</sup>
<b>Dimension stability</b>	ISO 23999/EN434	<0.1%
<b>Acoustical impact noise reduction</b>	EN ISO 717-2	
<b>Residual indentation</b>	ISO 24343-1/EN433	≤0.05 mm
<b>Abrasion resistance</b>	ISO 24338/EN660-2	Group T
<b>Castor chair continuous use</b>	ISO 4918/EN425	No effect
<b>Light fastness</b>	ISO 105-B02	≥6
<b>Flexibility</b>	ISO 24344/EN435	Ø 10 mm
<b>Resistance to chemicals</b>	ISO 26787/EN423	Very good
<b>Slip resistance</b>	DIN 51130	R10
<b>Electrical resistance</b>	EN1081	R1 > 1.10 <sup>9</sup> Ω
<b>Suitable for floor heating</b>	Yes	