

VINYL FLOOR CLEANING INSTRUCTIONS - Loose lay format, 5mm

Wiwax Emulsion contains detergent, waxes and polymers to effectively clean and maintain PVC, rubber, linoleum, asphalt, marble or slate flooring. This unique blend of ingredients cleans away the soil and leaves behind a protective, non-buffable, waterproof film.

Regular Maintenance: Mop and Bucket



Water	Number of Parts	ml/L	oz. / Gal.
Luke warm	1:32	30ml	4 oz

1. Dust mop or sweep floor
2. Clean off exterior and interior floor mats
3. Block areas to be cleaned. Floors will be slippery until dry
4. Add 4 oz. per gallon (30ml per liter) WIWAX to lukewarm water.
5. Mop floor clean with WIWAX with clean rayon-finish mop. Pick up soil and excess solution with tightly wrung out mop.
6. Do not rinse floor after cleaning
7. Let floor dry completely before allowing foot traffic back on floor

Regular Maintenance: Automatic Scrubbing Machines



Water	Number of Parts	ml/L	oz. / Gal.
Luke warm	1:64	15ml	2 oz

1. Dust mop or sweep floor
2. Clean off exterior and interior floor mats
3. Block areas to be cleaned. Floor will be slippery until dry
4. Add 2 oz. per gallon (15ml per liter) of WIWAX to lukewarm water.
5. Scrub floor using 3M red pad or soft nylon brush. Pick up any standing water left behind in the scrubbing process
6. DO NOT RINSE floor after cleaning
7. Let floor dry completely before allowing foot traffic back on floor