



Collection
format

Stained Concrete
Standard - 0.098" / 2.5mm

prefix
colors
architect folder

STC
4
Artistry Collection

Product description

construction	high performance commercial luxury vinyl tile
thickness	0.098" / 2.5mm
wear layer	.020" / 20 mil / 0.5mm
surface	polyurethane reinforced (PUR) top surface with glass bead technology
finish	smooth, matte
edge type	straight
installation method	direct glue-down
custom	custom sizes and gauges available
warranty	10 year commercial wear / 1 year manufacturing defect

Dimensions and packaging

	tile size	sq. ft. per piece	carton size	pieces per carton	weight per carton
square	24" x 24" / 609.6 x 609.6mm	4.0 ft ² / 0.372m ²	40 ft ² / 3.72m ²	10 squares	37.4 lb / 17 kg

ASTM and EN Technical standards

	ASTM and EN	result		ASTM and EN	result
wear group	EN 685	class 34,43	slip resistance	ASTM D2047 DIN 51130 EN 13893	ADA compliant R9 ≥ 0.3
chemical resistance	ASTM F925 EN 423	excellent excellent	residual indentation	ASTM F1700 EN 433	pass 0.05 mm
color fastness	ASTM F1515 ISO 105-B02-3	exceeds requirements ≥ 6	sound reduction	ASTM E90	SCT55 / IIC45
dimensional stability	ASTM F2199 EN 434	exceeds requirements ≤ 0.25%	smoke generation	ASTM E662	< 450
flexibility	ASTM F137 EN 435	pass pass	fire rating	ASTM E648 DIN 4102 EN 1350-1	class 1 B 1 B _{n-st}