



MAINTENANCE GUIDE

Initial Floor Preparation (Following Installation)

1. After 72 hours remove all surface soil/debris by sweeping or dust mopping
2. Scrub floor with TASKI Profi (4-6 oz. per gal. of hot water). Apply solution with a mop and bucket/wringer and allow to sit for five minutes. Use automatic scrubber for large areas or single disc low speed buffing machine for small areas. Use 3M red pads or soft nylon brush
3. Pick up soiled solution with wet vac or automatic scrubber
4. Rinse floor with clear water. Pick up solution with wet vac or automatic scrubber
5. Let floor dry completely before allowing foot traffic back on floor

Regular Maintenance: Mop and Bucket

1. Dust mop or sweep floor
2. Clean off exterior and interior floor mats
3. Block areas to be cleaned. Floors will be slippery until dry
4. Add 4 oz. per gallon (30ml per liter) WIWAX to lukewarm water. Mop floor clean with WIWAX with clean rayon-finish mop. Pick up soil and excess solution with tightly wrung out mop. Do not rinse floor after cleaning
5. Let floor dry completely before allowing foot traffic back on floor

Regular Maintenance: Automatic Scrubbing Machines

1. Dust mop or sweep floor
2. Clean off exterior and interior floor mats
3. Block areas to be cleaned. Floor will be slippery until dry
4. Add 2 oz. per gallon (15ml per liter) of WIWAX to lukewarm water. Scrub floor using 3M red pad or soft nylon brush. Pick up any standing water left behind in the scrubbing process

Interim Maintenance

After a period of several months, inclement weather or special circumstance (i.e. construction, parking lot resurface, etc.) it may be necessary to repeat initial cleaning process using the following PROFI dilution.

1. Dust mop or sweep floor
2. Clean off exterior and interior mats
3. Block areas to be cleaned. Floor will be slippery until dry
4. Add 5 oz. per gallon PROFI to lukewarm water. Apply to floor with a mop and bucket/wringer and machine scrub using a red pad
5. Rinse twice with clean water
6. Let floor dry

Restorative Maintenance

1. For technical support from LSI floors call 1.800.449.3916 between the hours of 8:30am and 5:00pm EST
2. For technical support from Wood Wyant call 1.800.361.7691 between the hours of 8:30am and 5:00pm EST

Tip and Suggestions

1. Do not use stripping pads or abrasive brushes
2. Use clean rayon-finish mops for WIWAX
3. Clean mops, machines and buckets after each use
4. Keep all mats vacuumed or cleaned
5. Do not burnish floor
6. For scuffs or oil marks, mix small amount PROFI 1:1 and use white pad or soft brush to spot clean floor
7. Do not use floor sealer on floor
8. Do not use high pH floor strippers or degreasers

Call LSI Floors to order more cleaning supplies: [1.800.449.3916](tel:1.800.449.3916)